



ROHS

物料	尺寸	长度
2x1	-	1.27
2x2	1.27	2.54
2x3	2.54	3.81
2x4	3.81	5.08
2x5	5.08	6.35
2x6	6.35	7.62
2x7	7.62	8.89
2x8	8.89	10.16
2x9	10.16	11.43
2x10	11.43	12.70
2x11	12.70	13.97
2x12	13.97	15.24
2x13	15.24	16.51
2x14	16.51	17.78
2x15	17.78	19.05
2x16	19.05	20.32
2x17	20.32	21.59
2x18	21.59	22.86
2x19	22.86	24.13
2x20	24.13	25.40
2x21	25.40	26.67
2x22	26.67	27.94
2x23	27.94	29.21
2x24	29.21	30.48
2x25	30.48	31.75
2x26	31.75	33.02
2x27	33.02	34.29
2x28	34.29	35.56
2x29	35.56	36.83
2x30	36.83	38.10
2x31	38.10	39.37
2x32	39.37	40.64
2x33	40.64	41.91
2x34	41.91	43.18
2x35	43.18	44.45
2x36	44.45	45.72
2x37	45.72	46.99
2x38	46.99	48.26
2x39	48.26	49.53
2x40	49.53	50.80
2x41	50.80	52.07
2x42	52.07	53.34
2x43	53.34	54.61
2x44	54.61	55.88
2x45	55.88	57.15
2x46	57.15	58.42
2x47	58.42	59.69
2x48	59.69	60.96
2x49	60.96	62.23
2x50	62.23	63.50




S0
0.40
0.46

Height
H=0.65mm, 1.0MM, 1.5mm, 1.7mm, 2.0mm, 2.5mm

Specification:
 Current Rating : 1AMP
 Temperature Range : -40°Cto+105°C
 Contact Resistance : 20mΩ Max
 Insulation Resistance : 1000MΩ Min
 Withstanding Voltage : AC 500V
 Material:
 Insulator : Polyester (UL94V-0)
 Standard: PBT/PACT/LCP
 Contact: Brass
 Plating : Au or Sn Over 50u" Ni

PCB LAYOUT



For reference only

REV. 1		2		3		4		5		6		7		8	
REVISION RECORD		DATE		SIZE: A4		0.000±0.08		X° X'±2°		SCALE: 1:1		NAME		DATE	
				UNIT: MM		0.00±0.15		X° ±3°		APPROVED					
										DESIGNER					
										DRAWN					
<p>深圳市联泰连接器有限公司 SHENZHEN UNICABLE CONNECTOR CO., LTD. 公司地址: WWW.SZLSTC.COM 公司邮箱: SZLSTC@126.COM 公司电话: 0755-23765650 公司传真: 0755-23765753</p>												PART NO: LSPH-0036		DWG. NO: ENDE0036	
TITLE: Dual In-Line Pin Header, Single Plastic, Pitch: 1.27mm												REV: A0		SHEET: 1/1	
Dual Row, Right Angle Type															