



# ROHS

料號	尺寸	尺寸
1X1	-	2.0
1X2	2.0	4.0
1X3	4.0	6.0
1X4	6.0	8.0
1X5	8.0	10.0
1X6	10.0	12.0
1X7	12.0	14.0
1X8	14.0	16.0
1X9	16.0	18.0
1X10	18.0	20.0
1X11	20.0	22.0
1X12	22.0	24.0
1X13	24.0	26.0
1X14	26.0	28.0
1X15	28.0	30.0
1X16	30.0	32.0
1X17	32.0	34.0
1X18	34.0	36.0
1X19	36.0	38.0
1X20	38.0	40.0
1X21	40.0	42.0
1X22	42.0	44.0
1X23	44.0	46.0
1X24	46.0	48.0
1X25	48.0	50.0
1X26	50.0	52.0
1X27	52.0	54.0
1X28	54.0	56.0
1X29	56.0	58.0
1X30	58.0	60.0
1X31	60.0	62.0
1X32	62.0	64.0
1X33	64.0	66.0
1X34	66.0	68.0
1X35	68.0	70.0
1X36	70.0	72.0
1X37	72.0	74.0
1X38	74.0	76.0
1X39	76.0	78.0
1X40	78.0	80.0
1X41	80.0	82.0
1X42	82.0	84.0
1X43	84.0	86.0
1X44	86.0	88.0
1X45	88.0	90.0
1X46	90.0	92.0
1X47	92.0	94.0
1X48	94.0	96.0
1X49	96.0	98.0
1X50	98.0	100.0
1X51	100.0	102.0
1X52	102.0	104.0




TYPE 1






TYPE 2

A±0.20



PCB LAYOUT



TYPE 2

For reference only

Specification:

Current Rating : 1.5AMP

Temperature Range : -40°C to +105°C

Contact Resistance : 20mΩ Max

Insulation Resistance : 1000MΩ Min

Withstanding Voltage : AC 500V

Material:

Insulator : Polyester (UL94V-0)

Standard: PACT/LCP

Contact: Brass

Plating : Au or Sn Over 50u" Ni

Height
H=1.0mm, 1.5mm, 2.0mm, 3.0mm

REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	SCALE: 1:1	NAME	DATE	TITLE: Pitch2.00mm Pin Header, Dual Plastic, Single Row, SMT Type	PART. NO: LSPH-0049
1	2	3	4	5	6	7	8			

GENERAL TOLERANCES

LINEAR

ANGLES

APPROVED

DESIGNER

DRAWN

UNIT: MM

0.0±0.25

X° REF±6°

X° ±3°

X° X'±2°

SHENZHEN UNICABLE CONNECTOR CO., LTD.

公司网址WWW.SZLSTC.COM

公司邮箱SZLSTC@126.COM

公司电话0755-23765650

公司传真0755-23765753

DRG. NO: ENDE0049

REV: A0

SHEET: 1/1